



9000 BTU PH PORTABLE



LOW NOISE



AUTO RESTART



EASY CLEANING
FILTER



ON/OFF TIMER

9000 BTU PH PORTABLE -PPT



New code			22020610001956
Sale model			MPPHB-09CRN7-QB6-N
Power supply		Ph-V-Hz	220-240V,1Ph,50Hz
Cooling	Capacity	W	2450
	Input	W	976
	Current	A	4,28
	EER	W/W	2,51
Moisture Removal		L/h	2,262
Rated input consumption		W	1200
Rated current		A	6,16
Starting current		A	18
Compressor	Model		DSM170V13UCZH
	Type		ROTARY
	Brand		GMCC
	Capacity	W	2525
	Input	W	765
	Rated current(RLA)	A	3,55
	Locked rotor Amp(LRA)	A	20
	Thermal protector		UP3-20
	Thermal protector position		INTERNAL
	Capacitor	uF	30.0
	Refrigerant oil	ml	XS-601C1 260
Indoor side fan motor	Model		YKTS-50-4-57L
	Capacitor	uF	4
	Speed(hi/mi/lo)	r/min	1040/960
Evaporator	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminum
	e.Tube outside dia.and type	mm	φ7,Inner groove tube
	f.Coil length x height x width	mm	240x231x40.11
	g.Number of circuits		2
Indoor side air flow (Hi/Mi/Lo)		m3/h	295/0/205
Indoor side noise level(Hi/Mi/Lo)		dB(A)	52/0/47.5
Sound power level (Hi)		dB(A)	63
Power consumption in thermostat-off mode		W	1
Power consumption in standby mode		W	0.5
Condenser	a.Number of rows		3.0
	b.Tube pitch(a)x row pitch(b)	mm	14.5x12.56
	c.Fin spacing	mm	1.2
	d.Fin type (code)		Unhydrophilic aluminium
	e.Tube outside dia.and type	mm	φ5,Inner groove tube
	f.Coil length x height x width	mm	240x261x37.68
	g.Number of circuits		2
Refrigerant type	Type		R290
	GWP		3
	Charged quantity	kg	0.17
	CO2 quantity	kg	0
Design pressure		MPa	2.6/1.0
Plug type			1.0x3/VDE
Control type			Remote Control
Operation temp (room temp.)		°C	17-35/
Application area (Cooling Standard)		m ²	12-18
Dimension (W*D*H)		mm	355x345x703
Packing (W*D*H)		mm	400x380x870
Net/Gross weight		Kg	24.7/27.3
Loading quantity 20' /40' /40'HQ		Pieces	174/356/534